
# WELKEN

We Provide the World with High Quality Products and Perfect Service



# WELKEN

Marst Safety Equipment (Tianjin) Co., Ltd

Tel: +86-22-88823317
Fax: +86-22-58712985
E-Mail:welken@chinawelken.com
marst@chinawelken.com
Web: www.chinawelken.com

www.chinamarst.com





Marst Safety Equipment (Tianjin) Co., Ltd

Marst Safety Equipment (Tianjin) Co., Ltd is the professional manufacturer who focus on research and development, production and sales of personal protective equipment. Our company holds the concept of "With quality to win credibility, science and technology to win the future" and always focus on brand building and products innovation. We own independent intellectual property rights and professional R&D team, dedicated to provide customers with quality services and one-stop solutions for personal safety protection.

Our factory was built in 1998. In 2007, in order to promote the products to the international market, Tianjin Bradi Security Equipment Co., Ltd, which has import and export right was established. We highly pay attention to customer's value and are committed to continuous products and services improvement.

We are also the Chinese supplier of Made-in-China and Alibaba. For more than ten years, we have actively promoted exchanges and cooperation with customers from all over the world through global professional exhibitions held in Germany, the United States and other areas. Our products are exported to more than 50 countries and regions. We have nearly 100 invention patents and utility models. The main products of safety lockout, eye wash stations, safety tripods have passed CE certificates, and eye wash stations also have ANSI certificates. We strive to create world-class levels products and provide work safety and security for more customers! In 2016, Tianjin Bradi Security Equipment Co., Ltd was recognized as a national high-tech enterprise. In 2019, in order to achieve leap-forward development, the company integrated its business into Marst Safety Equipment (Tianjin) Co., Ltd formed a scientific and technological manufacturing enterprise, which mainly integrates R&D, production, sales and technical services. It consists of five business segments: safety lockout, eye wash stations, safety tripods, intelligent shoe making machine and food machine.

God helps those who help themselves; great virtue can carry all things. Marst Safety Equipment (Tianjin) Co., Ltd has always been committed to continuous improvement and surpassing development, and is committed to providing more quality safety products to domestic and foreign customers.

#### ANSI certificate

#### **CE** certificate











#### **Patent certificate**














# WELKEN



Contents



# **WELKEN**



#### What is Lockout/Tagout?

In a locked way to avoid people operating isolated power sources or equipment casually until the isolation finished and the Lockout/ Tagout removed. By using Lockout Tags to warn people the isolated power sources or equipment cannot be operated casually.

#### Why use Lockout/Tagout?

1. Prevent accident, protect life; 2. Improve production efficiency; 3. Save cost.

#### Please use the Lockout/Tagout to lock the following power sources:

1. Power; 2. Hydraulic energy; 3. Pneumatic energy; 4. Gravity; 5. Chemical energy; 6. Heat; 7. Radiant energy.

#### Relevant laws and regulations:

Law of the People's Republic of China on Work Safety (November 2002)

Occupation Health and Safety Management Systems (December 2001)

Working Regulation of Power Safety (January 1987)

Safety Production License Regulations (March 2006)

Safety and Hygiene Regulations for Plant (May 1956)

Occupation Disease Prevention and Control Law (May 2002)

Occupation Health Supervision and Management Approach (May 2002)

National Mine Safety Law (November 1992)

Control of Hazardous Energy (Lockout/Tagout)(American OSHA,29CFR 1910.147)

Europe in Work Safety and Health Regulations (European OSHA)

National Standard for Plant [NOHSC:1010](Australian)

#### **Lockout/Tagout Procedures:**

1. Prepare for shutdown.

Identify the type of energy (power, machinery...) and potential hazards, locate the isolation devices and prepare to turn off the energy source.

2. Notification

Inform the relevant operators and supervisors who may be affected by isolating the machine.

3. Shut down

Shut down the machine or equipment.

4. Isolate the machine or equipment

Under necessary conditions, set isolation area for the machine or equipment which need Lockout/Tagout, such as warning tape, safety fence to isolate.

5. Lockout/Tagout

Apply Lockout/Tagout for hazardous power source.

6. Release hazardous energy

Release stocked hazardous energy, such as stocked gas, liquid. (Note: This step can operate before step 5, as per the actual situation to confirm.)

7. Verify

After Lockout/Tagout, verify the isolation of the machine or equipment is valid.

### Remove Lockout/Tagout Procedures:

1. Check tools, remove isolation facilities; 2. Check staff; 3. Remove Lockout/Tagout devices; 4. Inform relevant staff; 5. Restart equipment energy.

# WELKEN




Management

System

# The Function and Ways of Using the Key


## **Keyed to Differ**

Each padlock has unique key, padlock cannot open mutually.



### **Keyed Alike**

Within a group, all padlocks can open mutually, one key or several keys can open all padlocks in this group. Can customize several groups, between groups cannot open mutually.




#### Master&Differ

Within a group, each padlock just has unique key, padlock cannot open mutually, but one master key can open all padlocks in the group. Can customize several groups, different master keys between groups cannot open mutually.




#### Master&Alike

Within a group, all padlocks can open mutually, one key or several keys can open all padlocks in this group. Can customize several groups, between groups cannot open mutually. And if need open all groups padlocks, can add a master key.



01

# **Padlock Function**



# The Function and Ways of the Colors of the Key

The company can provide key shells of 16 different colors to collocate keys, making the functions of keys more powerful.

when it is opened, ensuring that the padlock will not be lost

- 1. For example, the supervisor's key covers black shell and the personal key without shell, so that when it is used, it can easily distinguish which is the supervisor key.
- 2. Different departments use different colors key. For example, the electrical maintenance department uses a key with a red shell with a red padlock, the locksmith department uses a key with a yellow shell with a yellow padlock, and the production department uses a key with a blue shell with a blue padlock. In this way, the color can distinguish which department is overhauling or which department's key, which facilitates the key management. The company can backup and archive the customer's padlock key according to the customer's request, so that the customer's key management system will be supplemented in the future which also can avoid the confusion of the original key management system.







## Safety Padlock

- ABS lock body is resistant impact, UV, corrosion, high and low temperature, shackle is heavy steel chrome plated, hard and beautiful.
- Lock body dimensions: Length 45mm, Width 40mm, Thickness 19mm; Shackle Diameter 6mm, Shacke Height 25mm, 38mm, 76mm three types to choose.
- Include 2 sets lock body warning labels, can write owner's information.
- 16 colors ABS lock body, convenient to choose.

Model	Description	Shackle Height
BD-8511	Keyed to differ,key-retaining	
BD-8512	Keyed alike,key-retaining	25mm
BD-8513	Master&alike,key-retaining	25111111
BD-8514	Master&differ,key-retaining	
BD-8521	Keyed to differ,key-retaining	
BD-8522	Keyed alike,key-retaining	38mm
BD-8523	Master&alike,key-retaining	3611111
BD-8524	Master&differ,key-retaining	
BD-8525	Keyed to differ,key-retaining	
BD-8526	Keyed alike,key-retaining	70
BD-8527	Master&alike,key-retaining	76mm
BD-8528	Master&differ,key-retaining	



03

Tel: +86-022-88823319 **WELKEN** 

- Meticulous workmanship, SUS304 material, beautiful, resistance corrosion and antirust
- Double leakage hole to prevent water accumulation, corrosion
- Arc edge design, grinding, good handle without cutting hands
- Thicker SUS304 shackle can prevent cutting, sawing; safety and reliability
- There are four specifications lock body to choose; each specification can collocate long shackle or short shackle.







BD-85A11

Model	Description	Size of Lock Body	Height of Shackle
BD-85A11	Keyed to differ, key-retaining		Clear height:21cm Diameter: 5mm
BD-85A12	Keyed alike, key-retaining	Width:30mm Height: 26mm	Distance: 15mm
BD-85A15	Keyed to differ, key-retaining	Thickness: 16mm	Clear height: 40cm
BD-85A16	Keyed alike, key-retaining		Diameter: 5mm Distance: 15mm

Model	Description	Size of Lock Body	Height of Shackle
BD-85A21	Keyed to differ, key-retaining		Clear height:26cm
BD-85A22	Keyed alike, key-retaining	Width:40mm Height: 32mm	Diameter: 7.2mm Distance: 20mm
BD-85A25	Keyed to differ, key-retaining	Thickness: 20mm	Clear height: 46cm Diameter: 7.2mm
BD-85A26	Keyed alike, key-retaining		Distance: 20mm

BD-85A15






		9	
9	30		59
30011008 50mm	38	2000 tas 576	38
50	1-20	50 _	120

BD-85A31

05

Model	Description	Size of Lock Body	Height of Shackle
BD-85A31	Keyed to differ, key-retaining		Clear height:30cm
BD-85A32	Keyed alike, key-retaining	Width:50mm Height: 38mm	Diameter: 9mm Distance: 23mm
BD-85A35	Keyed to differ, key-retaining	Thickness: 20mm	Clear height: 59cm Diameter: 9mm
BD-85A36	Keyed alike, key-retaining		Diameter: 9mm Distance: 23mm








Aluminum Padlock

- Suitable for chemical, automobile industry etc., light and solid, resistant chemical corrosion, high and low temperature,
   UV, and impact.
- Aluminum lock body, Chromium plated steel shackle, light and solid, bear a strong external force.
- Brass cylinder is more resistant corrosion, 6 cartridge cylinder improve the anti-lock by others.
- Provided eight colourful mental which include red, yellow, green, blue, black, purple, white, and orange
- Arc lock body design, height:40mm, width: 39mm, thickness: 19mm. Chromium plate steel shackle, height: 44mm and 78mm to choose, diameter: 6.35mm.

• Differ cylinder lockout, each lock can provide two keys, it also customize by the user.





BD-85B15

Http://www.chinawelken.com

BD-85A35

- ABS lock body and nylon shackle combined perfectly, with better non-conductive, anti-magnetism, explosion-proof quality.
- Nylon shackle is non-conductive, especially suitable for chemical industry, military, mining, power and flammable and explosive areas.
- Lock body dimensions: Length 45mm, Width 40mm, Thickness 19mm; Shackle Diameter 6mm, Shackle Height 38mm.
- All fittings of padlock are explosion-proof, anti-magnetism, insulation, corrosion-resistant.
- Include 2 sets lock body warning labels, can write owner's information.
- 16 colors ABS lock body, convenient to choose.

Model	Description	Shackle Material
BD-8531	Keyed to differ,key-retaining	
BD-8532	Keyed alike,key-retaining	Nylon
BD-8533	Master&alike,key-retaining	Trylon
BD-8534	Master&differ,key-retaining	



# Spark-proof Aluminum Safety Padlock

- ABS lock body is resistant impact, UV, corrosion, high and low temperature.
- Spark-proof aluminum shackle, anti-static, anti-magnetism, explosion-proof, corrosion-resistant.
- Lock body dimensions: Length 45mm, Width 40mm, Thickness 19mm; Shackle Diameter 6mm, Shackle Height 38mm.
- Include 2 sets lock body warning labels, can write owner's information.
- 16 colors ABS lock body, convenient to choose.



Model	Description	Shackle Material	
BD-8541	Keyed to differ,key-retaining		
BD-8542	Keyed alike,key-retaining	Spark-proof	
BD-8543	Master&alike,key-retaining	aluminum	
BD-8544	Master&differ,key-retaining		

## Brass Shackle Safety Padlock

- ABS lock body is resistant impact, UV, corrosion, high and low temperature.
- Brass shackle, anti-static, anti-magnetism, explosion-proof, corrosion-resistant.
- Lock body dimensions: Length 45mm, Width 40mm, Thickness 19mm; Shackle Diameter 6mm, Shackle Height 38mm.
- Include 2 sets lock body warning labels, can write owner's information.
- 16 colors ABS lock body, convenient to choose.

07


Model	Description	Shackle Material	
BD-8551	Keyed to differ,key-retaining		
BD-8552	Keyed alike,key-retaining	D	
BD-8553	Master&alike,key-retaining	- Brass	
BD-8554	Master&differ,key-retaining		



## Laminated Steel Safety Padlock

- WELKEN laminated padlock is suitable for using special environment.
- Can stick obvious warning labels on lock body, easy to identify and manage.
- Lock body is made of high resistance steel layer, shackle is high resistance steel with plating layer, hard and durable.
- Lock body dimensions: Length 36.2mm, Width 40mm, Thickness 23.5mm.
- The board on lock body for label, 8 colors to choose, easy to identify.

Model	Description	Shackle Height	
BD-8561	Keyed to differ,key-retaining	27	
BD-8562	Keyed alike,key-retaining	- 27mm	
BD-8565	Keyed to differ,key-retaining	46	
BD-8566	Keyed alike,key-retaining	46mm	



# Long Lock Body Safety Padlock

- ABS lock body is resistant impact, UV, corrosion, high and low temperature.
- Lock body dimensions: Length 80mm, Width 40mm, Thickness 19mm.
- Shackle is high resistance steel with plating layer, hard and beautiful.
- Include 2 sets lock body warning labels, can write owner's information.
- 16 colors ABS lock body, convenient to choose.

Model	Description	Shackle Height
BD-8571	Keyed to differ,key-retaining	
BD-8572	Keyed alike,key-retaining	29
BD-8573	Master&alike,key-retaining	- 38mm
BD-8574	Master&differ,key-retaining	]
BD-8575	Keyed to differ,key-retaining	
BD-8576	Keyed alike,key-retaining	76
BD-8577	Master&alike,key-retaining	- 76mm
BD-8578	Master&differ,key-retaining	1



- ABS lock body is resistant impact, UV, corrosion, high and low temperature.
- Lock body dimensions: Length 45mm, Width 36.5mm, Thickness 16.5mm, shackle diameter 5mm.
- Shackle is made of 316 stainless steel, anti-acid, anti-alkali, anti-corrosion of many types of chemicals.
- Include 2 sets lock body warning labels, can write owner's information.

Model	Description	Shackle Height
BD-8581	Keyed to differ,key-retaining	38mm
BD-8582	Keyed alike,key-retaining	3011111



# ABS Dust-proof Safety Padlock

- ABS lock body is resistant impact, UV, corrosion, high and low temperature.
- Lock body dimensions: Length 45mm, Width 40mm, Thickness 19mm, shackle diameter 6 mm.
- The sealer to block keyhole is PP, soft and durable, good sealing.
- Include 2 sets lock body warning labels, can write owner's information.

Model	Description	Shackle Height
BD-8591	Keyed to differ,key-retaining	
BD-8592	Keyed alike,key-retaining	38mm
BD-8593	Master&alike,key-retaining	3011111
BD-8594	Master&differ,key-retaining	





# **WELKEN**

# **PVC** Tags

- PVC material, sunscreen ink printing, suitable for outdoor.
- 10 pieces per bag.
- Can customize as per customers' requests.

#### Regular Type





BD-8611 PVC Tags Length:145mm Width: 75mm Thickness:0.8mm Keyhole diameter: 8mm

#### **Customize Type**

















# Safety Signs

BD-8621 PVC Warning Signs Material: PVC Printing requests: dimensions and content can customize as per requests. BD-8622 Sticky Warning Signs Material: Sticky Printing requests: dimensions and content can customize as per requests.

























