

European Standard Two-phase Plug Lockout

- Be made of ABS resin, patent protection product.
- Stick with sunscreen label can write the name of the person in charge and matters.
- Use with professional safety padlock and tag together.

Model	Description
BD-8186	Applicable 220V two-phase round plug and European standard power plug



Trapezoidal Plug Lockout

- Be made of ABS resin, trapezoidal plug lockout, patent protection product.
- Use with professional safety padlock and tag together.



Model	Description
BD-8187	Provide lock protection for the computer host and electrical equipment

Crane Lift Controller Lockout Bag

- Made of sewing tear-resistant nylon fabric, length 450mm, width 250mm.
- There is a PVC barrier in the bag to prevent people from accidentally starting the controller button.
- The bag surface is marked with warning sign.
- Use with professional safety padlock and tag together.



BD-8191




BD-8192



Model	Description
BD-8191	External dimensions: Length 450mm, Width 250mm
BD-8192	External dimensions: Length 450mm, Width 250mm

Ball Valve Lockout

- Be made of high strength polypropylene, excellent anti-fracture, wear resistance and insulation performance.
- Can adjust the position of the padlock arbitrarily, convenient and quick.
- Use with professional safety padlock and tag together.



Model	Description
BD-8211	External dimensions: Length 208mm, Width 77mm, Height 130mm

Rotation Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, durable and resistance to chemicals, corrosion resistance.
- Unique design to lock the ball valve from which handle can be removed.
- Use with professional safety padlock and tag together.



Model	Description
BD-8214	Suitable for handle up to 34mm X 49mm

Step 1: orthogonal



Step 2: screw tightly



Step 3: lock



Single Arm Universal Ball Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, with better impact resistance and excellent chemical resistance.
- Advanced trapezoidal upper teeth improves the bite strength of valve handle.
- The rotating arm makes the bite more tight and improves the safety performance.
- Two gear adjustable
- Use with professional safety padlock and tag together.



Model	Description
BD-8212	External dimensions: Length 205mm, Width 50mm, Height 275mm Suitable for handle width 19mm-46mm, suitable for handle maximum thickness 25mm, rotating arm length 170mm



Double Arms Universal Ball Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, with better impact resistance and excellent chemical resistance.
- Advanced trapezoidal upper teeth improves the bite strength of valve handle.
- The rotating arm makes the bite more tight and improves the safety performance.
- Two gear adjustable
- Use with professional safety padlock and tag together.



Model	Description
BD-8213	External dimensions: Length 375mm, Width 50mm, Height 275mm Suitable for handle width 19mm-46mm, suitable for handle maximum thickness 25mm, rotating arm length 170mm

New Design Resin Valve Lockout

- Be made of impact resistant ABS, corrosion resistance and better insulation performance.
- One-piece design, can lock the small right angle rotating ball valve in closed position.
- With a knob can tighten directly to install, easy to use, without assistant tools.
- Use with professional safety padlock and tag together.
- Suitable for locking 1/4"~1 " ball valve handle in closed condition.



Model	Description
BD-8215	External dimensions: Length 90mm, Width 77mm, Height 78mm



New Design Metal Valve Lockout

- Heavy steel with painting.
- Easy to use, one-piece design, can lock the right angle turning ball valve in closed position.
- With a knob can tighten directly to install, easy to use, without assistant tools.
- Use with professional safety padlock and tag together.
- Suitable for locking 1 1/4"~2.5 " ball valve handle in closed condition.



Model	Description
BD-8216	External dimensions: Length 200mm, Width 18mm, Height 130mm



Butterfly Valve Lockout

- Be made of high strength polypropylene, excellent anti-fracture, wear resistance and insulation performance.
- Can adjust the position of the padlock arbitrarily, convenient and quick.
- Suitable for butterfly valve size: 0.25" - 2.5".
- Use with professional safety padlock and tag together.



Model	Description
BD-8221	External dimensions: Length 300mm, Width 106mm, Height 67mm

Step 1: Orthogonal



Step 2: Merge



Step 3: Lock



Universal Butterfly Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, with better impact resistance and excellent chemical resistance.
- Advanced trapezoidal upper teeth improves the bite strength of valve handle.
- The stainless steel T-shape wedge fixes the butterfly valve jaw firmly.
- Use with professional safety padlock and tag together.

Model	Description
BD-8222	Suitable for handle width 19mm-46mm, suitable for handle maximum thickness 25mm

Step 1



Step 2



Step 3



Gate Valve Lockout

- It is high strength ABS injection molding, with better high temperature resistance, corrosion resistance, impact resistance and insulation performance.
- Working temperature: -20℃-80℃;
- Unique design of central bulge, after removing, can be used for lifting rod gate valve.
- According to the handle diameter, there are 5 specifications lockout to choose.
- Stick with a warning label and indicate the application scope.
- Half moon flat box design, can completely lock the valve handle to prevent misoperation.
- Use with professional safety padlock and tag together.



Model	Description
BD-8231	Suitable for the handle diameter: 25mm-63mm, back hole diameter: 19mm, disassembled circular hole diameter: 19mm
BD-8232	Suitable for the handle diameter: 63mm-127mm, back hole diameter: 32mm, disassembled circular hole diameter: 32mm
BD-8233	Suitable for the handle diameter: 127mm-165mm, back hole diameter: 53mm, disassembled circular hole diameter: 53mm
BD-8234	Suitable for the handle diameter: 165mm-254mm, back hole diameter: 70mm, disassembled circular hole diameter: 70mm
BD-8235	Suitable for the handle diameter: 254mm-330mm, back hole diameter: 70mm, disassembled circular hole diameter: 70mm

Universal Gate Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, with better impact resistance and excellent chemical resistance.
- Suitable for the maximum thickness of the handle 25mm, applicable temperature -20℃ -160℃.
- Advanced trapezoidal upper teeth and opening design lower teeth are easy to hitch the valve handle and improve the bite strength of valve handle.
- Use with professional safety padlock and tag together.




Model	Description
BD-8236	1.5m, 2.5m, 3.5m cable are available to choose





BD-8237



BD-8238



Universal Valve Lockout

- Be made of reinforced nylon PA6 and stainless steel, with better impact resistance and excellent chemical resistance.
- Suitable for handle width 46mm, maximum thickness 22mm, applicable temperature -20 °C -160 °C.
- BD-8237 has adjustable arm, can adjust the length of the arm according to customers' requests.
- Use with professional safety padlock and tag together.

Model	Description
BD-8237	Can lock most of the ball valve, butterfly valve, gate valve
BD-8238	Can lock most of the butterfly valve, gate valve

Pneumatic Lockout

- Be made of stainless steel, better antirust and corrosion resistance performance.
- Can lock air interface diameter 19mm, 15.5mm, 13.5mm, 12mm, 10.5mm, 9.5mm, 8mm, 6.5mm.
- Can lock air interface to prevent the air from being reconnected.
- External dimensions: Length 206mm, Width 33mm, Thickness 2.6mm.



BD-8241



Pressurized Gas Cylinder Valve Lockout



BD-8251

- Be made of high strength industrial ABS resin, with better impact resistance, chemical pollution resistance.
- Lock the gas cylinder high pressure valve, prevent to open, suitable for valve with limiter.
- Applicable to all gas cylinder high pressure valves, valve diameter range can up to 76mm.
- External dimensions: 152mm X 97mm

Hasp Lockout

- Install the hasp lockout on the energy cut off switch so that the equipment cannot be operated during maintenance. multiple people can be locked at the same time.
- The equipment cannot be turned on unless the last person opens his/her padlock.



BD-8311
1"Hasp Lock
with 6 Holes



BD-8312
1.5"Hasp Lock
with 6 Holes



BD-8313
Insulation Hasp
Lock with 6 Holes



BD-8314
Hasp Lock
with 8 Holes

Model	Keyhole Quantity	Material	Jaw Size
BD-8311	6	Steel jaw, polypropylene injection handle	1"
BD-8312	6	Steel jaw, polypropylene injection handle	1.5"
BD-8313	6	ABS resin lock body and PA6 lock shackle, insulation, anti-chemical, anti-magnetic and non-conductive	78mm X 18mm
BD-8314	8	Zinc alloy, polypropylene injection handle	1.5"

New Aluminum Hasp Lockout

NEW!



BD-8317
1"Aluminum Hasp
Lock with 6 Holes

BD-8318
1.5"Aluminum Hasp
Lock with 6 Holes

- Install the hasp lockout on the energy cut off switch so that the equipment cannot be operated during maintenance.
- The equipment cannot be turned on unless the last person opens his/her padlock.
- Can accommodate 6 people to lock, multiple people can be locked at the same time.

Model	Description	Jaw Size
BD-8317	Spark-proof aluminum jaw, polypropylene injection handle	1"
BD-8318	Spark-proof aluminum jaw, polypropylene injection handle	1.5"